

Thermal flywheel

KSI

Capacity 25-50-100-200 L

Features

Long life without corrosion

Easy installation

Tax incentives*



Buffer tanks

Construction features

KSI – Technical water tank

Tank for heating and cooling water as a thermal flywheel or hydraulic separator, in raw steel painted externally with external insulation in injected rigid polyurethane, 50 mm thick.

Technical data

MODEL		KSI – 25	KSI – 50	KSI – 100	KSI – 200
Available volume	l	24	58	126	203
Maximum operating pressure	bar	6	6	6	6
DIMENSIONS AND WEIGHTS		KSI – 25	KSI – 50	KSI – 100	KSI – 200
Diameter	mm	380	400	500	550
Total height	mm	455	935	1095	1395
Empty weight	kg	18	25	35	45
ENERGY CLASS		KSI – 25	KSI – 50	KSI – 100	KSI – 200
Losses through dispersion	W	19	34	50	68
Energy class		A	B	B	C

Regulations (EU) No.812/2013 and No.814/2013.



RHOSS S.P.A.
Via Oltre Ferrovia, 32
33033 Codroipo (UD) - ITALY
tel. [+39 0432 911611](tel:+390432911611)
rhoss@rhoss.com

rhoss.com

RHOSS S.P.A. non si assume alcuna responsabilità per eventuali errori del presente stampato e si ritiene libera di variare senza preavviso le caratteristiche dei propri prodotti.